Thank you for purchasing this Dynojet kit. This kit has been developed for a motorcycle which is set to the parameters listed at the right in the "Stage" description. If your motorcycle does not meet any of these parameters please check with Dynojet before installation. For technical assistance contact your Dynojet distributor or call Dynojet U.S.A. (800)-992-4993

> 2191 Mendenhall Dr. Suite 105 North Las Vegas, NV 89031 TEL: 702-399-1423 FAX: 702-399-1431 8am-5pm Pacific Time Monday through Friday

> > Website Address http://www.dynojet.com

The manufacturer and seller make no warranties express or implied which extend beyond the description of the goods contained herein. Any description of this product is for the purpose of identifying it and shall not be deemed to create an express warranty.




## E1330.001

**European Models Only** 

1983-87 Honda XL600

## Stage 3

For mildly tuned machines using the stock airbox, with stock or K&N filter. May also be used with a good aftermarket exhaust system K&N filter #N/A



## WARNING

NO SMOKING! NO OPEN FLAME! WHILE INSTALLING YOUR DYNOJET KIT

Parts List		
1	Main Jet	DJ124
1	Main Jet	DJ128
1	Main Jet	DJ132
2	Fuel Needles	DNO110
2	Adjusting Washers	DW0001
2	E-Clips	DE0001

## STAGE THREE INSTRUCTIONS

- 1. Use the stock main jet in the right carb.
- 2. Use the DJ128 main jet in the left carb.
- 3. Use the DJ124 main jet or the DJ132 main jet as alternate main jets.
- 4. Use the (2) DNO110 K&N needles supplied with the E-clips installed on groove #1.
- 5. Set air screws for smoothest idle and transition.
- 6. Remove or modify the air box lid.

