

Q202.001
1995-2001 Kawasaki
KEF300 Lakota

STAGE 1

For mildly tuned machines using the stock airbox, with stock or aftermarket filter. May also be used with a good aftermarket exhaust system. K&N Filter # KA-2587.

PARTS LIST		
1	Main Jet	DJ126
1	Main Jet	DJ130
1	Main Jet	DJ134
1	Main Jet	DJ138
1	Fuel Needle	DNO106
2	Adjusting Washer	DW0001
1	E-Clip	DE0001
1	Slide Drill	DD#37

STAGE ONE INSTRUCTIONS

1. Remove vacuum slide from carb. Remove stock needle & spacers, noting order of assembly.
2. Using the drill provided (#37) enlarge your stock slide lift hole.
3. Install Dynojet needle on groove #3 for applications below 5000 feet, groove #2 for above 5000 feet, using all stock spacers. Install the Dynojet washers above the E-clip.
4. Remove stock main jet and replace with Dynojet main provided. Use the DJ134 below 3000 feet, DJ130 from 3000 to 6000 feet and DJ126 above 6000 feet. If you are running an aftermarket exhaust, use the DJ138 below 3000 feet, DJ134 from 3000 to 6000 feet and the DJ130 above 6000 feet. Be sure that the jet you are changing is the main jet.
5. Locate the Fuel Mixture Plug(Fig. B), using a flat blade screwdriver carefully turn mixture screw clockwise until seated, then back out 2-1/2 turns.

