

Q204.001
1991-2001 Kawasaki 220
Bayou
STAGE 1

For mildly tuned machines using the stock airbox, with stock or aftermarket filter. May also be used with a good aftermarket exhaust system. K&N Filter # KA-2288.

PARTS LIST		
1	Main Jet	DJ104
1	Main Jet	DJ108
1	Main Jet	DJ112
1	Fuel Needle	DNO170
1	Adjusting Washer	DW0001
1	E-Clip	DE0001

STAGE ONE INSTRUCTIONS

1. Unscrew the carb top. Disconnect throttle cable and remove the slide. Remove needle retainer.(Fig.A).
2. Install Dynojet needle on groove# 4 for applications below 5000 feet, groove #3 for above 5000 feet, using all stock spacers. Install the Dynojet washer above the E-clip.
3. Remove stock main jet and replace with Dynojet main provided. Use the DJ112 below 3000 feet, DJ108 from 3000 to 6000 feet and DJ1104 above 6000Feet. Be sure that the jet you are changing is the main jet.
4. Locate the Fuel Mixture Screw. Using a flat blade screwdriver, turn the mixture screw clockwise until it seats, then turn out 1 1/2 turns .




Fig. A

This is the Fuel Mixture Screw.

Fig. B

