

Q403.001
1996-2005 Yamaha
350 Wolverine
Stage 1

For mildly tuned machines using the stock airbox with stock or aftermarket filter. May also be used with a good aftermarket exhaust system.

<i>Parts List</i>		
1	Main Jet	DJ144
1	Main Jet	DJ150
1	Main Jet	DJ155
1	Main Jet	DJ160
1	Fuel Needle	DNO360
1	Slide Drill	DD 32
1	Adjusting Washer	DW0001
1	E-Clip	DE0001

STAGE ONE INSTRUCTIONS

1. Remove vacuum slide from the carb. Remove stock needle & spacers, noting order of assembly.
2. Locate the slide lift hole (Fig. A). Use the (DD32) drill provided to enlarge slide lift hole (Fig. A).
3. Install Dynojet needle on groove #4 for applications below 5000 feet, groove #3 for above 5000 feet, using all stock spacers. Install the Dynojet washer above the E-clip.
4. Remove the stock main jet and replace with the Dynojet main jet provided. When using the stock exhaust use, the DJ155 below 3000 feet, DJ150 from 3000 to 6000 feet and DJ144 above 6000 feet. When using an aftermarket exhaust, use the DJ160 below 3000 feet, DJ155 from 3000 to 6000 feet and DJ150 above 6000 feet. Be sure that the jet you are changing is the main jet (Fig. B).
5. Locate the Fuel Mixture Screw (Fig. B). Using a flat blade screwdriver, turn the mixture screw clockwise until it seats, then turn out 2 1/2 turns.

